



Wheeler-Rex Model 363020 Fire Hose Tester

SPECIFICATIONS

DIMENSIONS:	38" (95cm) L x 30" (75 cm) W x 24" (60cm) H
WEIGHT:	128 lbs / 58 kg
PUMP:	Piston pump: Positive Displacement Capacity: 3gpm, 10lpm Pressure: Maximum pressure 500psi(34 bar) Lubrication: Chassis Grease
MOTOR	1hp, 115V single phase, 60hz, TEFC
INLET:	One 2-1/2"NST Female Swivel Coupling (quick fill)
OUTLET:	Two independent ball valves with 2-1/2" NST Male Couplings
CONTROL:	Adjustable pressure relief valve
GAUGE:	Glycerin filled, 0 – 1000psi, (70 bar) stainless steel



FEATURES

- Meets testing standards as set forth in the NFPA Guidelines
- Can test one or two hoses - independently controlled
- Full perimeter cage mounted on swivel casters
- 2-1/2" NST "Quick Fill" Inlet



Wheeler-Rex Model 363040 Fire Hose Tester

SPECIFICATIONS

DIMENSIONS:	38" (95cm) L x 30" (75 cm) W x 24" (60cm) H
WEIGHT:	145 lbs / 66 kg
PUMP:	Piston pump: Positive Displacement Capacity: 3gpm, 10lpm Pressure: Maximum pressure 500psi(34 bar) Lubrication: Chassis Grease
MOTOR	1hp, 115V single phase, 60hz, TEFC
INLET:	One 2-1/2"NST Female Swivel Coupling (quick fill)
OUTLET:	Four independent ball valves with 2-1/2" NST Male Couplings
CONTROL:	Adjustable pressure relief valve
GAUGE:	Glycerin filled, 0 – 1000psi, (70 bar) stainless steel



FEATURES

- Meets testing standards as set forth in the NFPA Guidelines
- Can test single or multiple hoses - independently controlled
- Full perimeter cage mounted on swivel casters
- 2-1/2" "Quick Fill" Inlet