

Wheeler Model 36454 Hydrostatic Test Pump SPECIFICATIONS

| DIMENSIONS: | 24" (61cm) L x 19" (48cm) W x 19.5" (50cm) H |
|--------------------|---|
| WEIGHT: | 135 lbs 61.5 kg |
| PUMP: | Twin piston: Positive displacement type Inlet and Outlet Ports: 3/4 " NPT |
| | Capacity: 10gpm, 38 ltr/min |
| | Max Pressure: 400psi (27 bar) |
| | Operating Speed: 600rpm |
| | Lubrication: Chasis grease |
| | Shaft Size: 1" diameter |
| ENGINE | 6.5hp Briggs & Stratton Intek Pro, 4 cycle, gasoline |
| | powered, with 6-1 gear reduction |
| CONTROL: | Adjustable pressure relief valve |
| PULSATION CONTROL: | Pulse Hose |
| GAUGE: | Glycerin filled, 0-600psi (41 bar) |
| DISCHARGE HOSE: | 3/4" x 10' (3m), rated 1000psi (68 bar) working |
| | pressure |
| INTAKE HOSE: | 34" x 10' (3m) with strainer |



FEATURES

- ✓ Automatic and precise pressure build-up
- ✓ Isolates and maintains high pressure.
- √ Adjustable automatic by-pass
- ✓ Constant volume at all pressure
- ✓ Durability
- ✓ Full perimeter cage with rubber padded feet