



Wheeler Model 46301 Hydrostatic Test Pump SPECIFICATIONS

DIMENSIONS: Packed	27" (67.5cm) L x 22" (55cm) W x 34" (85cm) H
WEIGHT:	132 lbs., 60 kg
PUMP:	Roller: Variable Displacement Inlet and outlet ports: 3/4" Capacity: 11.4 – 5.4gpm, 43 – 20.5 ltr/min Max Pressure: 300psi (20.5 bar) Operating Speed: 600rpm Operating Temp.: 140 degree F max Lubrication: Factory lubed sealed bearings Shaft Size: 5/8"
CONTROL:	Adjustable pressure relief valve
ENGINE:	6.5hp Briggs & Stratton Intek Pro, 4 cycle, gasoline powered, with 6 – 1 gear reduction
GAUGE:	Glycerin filled, 0 – 600psi, 0 – 42 kg/cm, bottom mount
DISCHARGE HOSE:	3/4" x 10' (3m), rated 1000psi (68 bar) working pressure
INTAKE HOSE:	3/4" x 10' (3m) with strainer

FEATURES



- ✓ Economical
- ✓ Easy maintenance
- ✓ Adjustable pressure control
- ✓ On two wheeled cart with pneumatic tires
- ✓ Inline strainer with stainless steel mesh filter and clear bowl