



Wheeler-Rex Model 46501 Hydrostatic Test Pump

SPECIFICATIONS

DIMENSIONS:	28" (70cm) L x 24" (60cm) W x 35" (87.5cm) H
WEIGHT:	136 lbs. 62 kg
PUMP:	Triple Diaphragm: Positive Displacement Ports: 1" inlet ; 3/4" NPT outlet Capacity: 10gpm, 38lpm Pressure: 0-500psi Operating Speed: 550rpm Lubrication: Pump 40W Non-detergent Oil - 20 ounces Gear case 80/90W Gear Oil – 16 ounces Shaft Size: 1"
ENGINE:	6.5hp Briggs & Stratton Intek Pro, 4 cycle, gasoline
CONTROL:	0 – 500psi adjustable pressure relief valve
GAUGE:	Glycerin filled, 0 – 600psi, 0-42kg
DISCHARGE HOSE:	3/4" x 10' (3m) 1000psi rated
INLET HOSE:	3/4" x 10' (3m) with strainer



FEATURES

- Able to handle up to 10% chlorine solution.
- Automatic and precise pressure build-up.
- Isolates and maintains high pressure.
- Automatic by-pass.
- Constant volume.
- Adjustable pressure control.
- On two-wheeled cart with pneumatic tires.
- Inline strainer with stainless steel mesh filter and clear bowl.