



Wheeler Model 47100 Electric Test Pump SPECIFICATIONS

DIMENSIONS:	28" (70cm) L x 17" (42.5cm) W x 35" (87.5 cm) H
WEIGHT:	96 lbs. 44 kg
PUMP:	Triplex Piston: Positive Displacement Inlet and outlet ports: 3/8" NPT Capacity: 2.2gpm, 7.6lpm Pressure: 1000psi (68 bar) max Operating Speed: 3450rpm Operating Temp.: 160 degree F max Lubrication: Continuous oil bath, 11.83oz Special Cat Pump Oil Shaft Size: 5/8" diameter
MOTOR:	1½hp, 115/220V Electric 60hz
CONTROL:	Adjustable pressure relieve valve
GAUGE:	Glycerin filled, 0 – 2000psi (136 bar)
DISCHARGE HOSE:	½" x 10' (3m), rated 2000psi (136 bar) working pressure
INLET HOSE:	¾" x 10' (3m) with strainer

FEATURES



- Automatic and precise pressure build-up
- Single control sets pressure, provides automatic unloading and isolates and maintains pressure
- Continuous pump lubrication
- Adjustable pressure control
- On two wheeled cart with pneumatic tires
- Inline strainer with stainless steel mesh filter and clear bowl



Wheeler Model 47101 Electric Test Pump SPECIFICATIONS

DIMENSIONS:	28" (70cm) L x 17" (42.5cm) W x 35" (87.5 cm) H
WEIGHT:	96 lbs. 44 kg
PUMP:	Triplex Piston: Positive Displacement Inlet and outlet ports: 3/8" NPT Capacity: 2.2gpm, 7.6lpm Pressure: 1000psi (68 bar) max Operating Speed: 3450rpm Operating Temp.: 160 degree F max Lubrication: Continuous oil bath, 11.83oz Special Cat Pump Oil Shaft Size: 5/8" diameter
MOTOR:	220V, 50hz
CONTROL:	Adjustable pressure relieve valve
GAUGE:	Glycerin filled, 0 – 2000psi (136 bar)
DISCHARGE HOSE:	1/2" x 10' (3m), rated 2000psi (136 bar) working pressure
INLET HOSE:	3/4" x 10' (3m) with strainer

FEATURES



- Automatic and precise pressure build-up
- Single control sets pressure, provides automatic unloading and isolates and maintains pressure
- Continuous pump lubrication
- Adjustable pressure control
- On two wheeled cart with pneumatic tires
- Inline strainer with stainless steel mesh filter and clear bowl



Wheeler Model 47102 Electric Test Pump SPECIFICATIONS

DIMENSIONS:	28" (70cm) L x 17" (42.5cm) W x 35" (87.5 cm) H
WEIGHT:	96 lbs. 44 kg
PUMP:	Triplex Piston: Positive Displacement Inlet and outlet ports: 3/8" NPT Capacity: 1.1gpm, 3.8lpm Pressure: 0 – 2000psi (140 bar) Operating Speed: 3450rpm Operating Temp.: 160 degree F max Lubrication: Continuous oil bath, 11.83oz Special Cat Pump Oil Shaft Size: 5/8" diameter
MOTOR:	115/220V Electric 60hz
CONTROL:	Adjustable pressure relief valve
GAUGE:	Glycerin filled, 0 – 3000psi
DISCHARGE HOSE:	1/2" x 10' (3m), rated 2000psi (136 bar) working pressure
INLET HOSE:	3/4" x 10' (3m) with strainer

FEATURES



- ✓ Automatic and precise pressure build-up
- ✓ Single control sets pressure, provides automatic unloading and isolates and maintains pressure
- ✓ Continuous pump lubrication
- ✓ Adjustable pressure control
- ✓ On two wheeled cart with pneumatic tires
- ✓ Inline strainer with stainless steel mesh filter and clear bowl